

Dimension4 System Comparison Data

System	Sön	Sön Plus	Project	Ensemble2
Includes Absorbers	✓	✓	✓	✓
Wall Absorber Depth	2"	4"	4"	4" & 6"
Absorber Operating Range	500 Hz to 20kHz	250 Hz to 20kHz	200 Hz to 20kHz	200 Hz to 20kHz
Includes Bass Absorbers	✓	✓	✓	✓
Includes Ceiling Absorbers	✓	✓	✓	✓
Ceiling Absorber Depth	1"	1"	1"	1"
Tapered HF Absorption	—	—	—	✓
Includes Diffusers	✓	✓	✓	✓
2D Diffusion	✓	✓	✓	✓
2D Diffuser Depth	2"	4"	4"	6"
3D Diffusion	✓	✓	—	✓
3D Diffuser Depth	2"	4"	—	6"
Wood Diffusers	—	—	—	✓
Includes Ceiling Diffusers	✓	✓	—	✓
Diffuser Operating Range	1000 Hz to 5kHz	500 Hz to 5kHz	500 Hz to 5kHz	350 Hz to 8kHz
Diffusers Incorporate Bass Absorption	—	—	—	✓
Recommended for Surface Mounting	—	—	✓	✓
Recommended Behind Stretch Fabric	✓	✓	—	✓
Price Range	Mid to Low	Intermediate	Mid to High	High
Usual Applications	Recording and Project Studios	Recording and Project Studios	Recording and Project Studios	Recording and Project Studios
Colors	38	38	38	4
Fire Rated	✓	✓	✓	✓
Mold Rated	✓	✓	✓	✓
NRC	0.9	1.0	1.2	1.2
Bracket Mounts	—	—	✓	✓